

# Silica Sand #60

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations  
Issue date: 2/27/2026 Version: 1.0

### SECTION 1 Identification

#### 1.1. Product identifier

Product form : Substance  
Substance name : Silica Sand #60  
Product code : M80060

#### 1.2. Other means of identification

No additional information available

#### 1.3. Recommended use of the chemical and restrictions on use

No additional information available

#### 1.4. Supplier's details

No additional information available

#### 1.5. Emergency phone number

No additional information available

### SECTION 2 Hazard Identification

#### 2.1. Classification of the substance or mixture

##### GHS US classification

Serious eye damage/eye irritation, Category 2B	H320	Causes eye irritation.
Carcinogenicity, Category 1A	H350	May cause cancer.
Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation	H335	May cause respiratory irritation.
Specific target organ toxicity — Repeated exposure, Category 2	H373	May cause damage to organs through prolonged or repeated exposure.

Full text of H statements : see section 16

#### 2.2. Label elements

##### GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Danger

Hazard statements (GHS US) : H320 - Causes eye irritation  
H335 - May cause respiratory irritation  
H350 - May cause cancer.  
H373 - May cause damage to organs through prolonged or repeated exposure

Precautionary statements (GHS US) : P201 - Obtain special instructions before use.  
P202 - Do not handle until all safety precautions have been read and understood.  
P260 - Do not breathe dust, fume, gas, mist, vapors, spray.  
P264 - Wash hands, forearms and face thoroughly after handling.  
P271 - Use only outdoors or in a well-ventilated area.  
P280 - Wear protective gloves, protective clothing, eye protection, face protection, and hearing protection.  
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.

# Silica Sand #60

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308+P313 - If exposed or concerned: Get medical advice/attention.  
P312 - Call a poison center or doctor if you feel unwell.  
P314 - Get medical advice or attention if you feel unwell.  
P337+P313 - If eye irritation persists: Get medical advice or attention.  
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.  
P405 - Store locked up.  
P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

### 2.3. Hazards associated with known or reasonably anticipated uses

No additional information available

### 2.4. Hazards not otherwise classified

No additional information available

### 2.5. Unknown acute toxicity

No additional information available

## SECTION 3 Composition/information on ingredients

### 3.1. Substances

Name : Silica Sand #60

Name	Product identifier	%	GHS US classification
quartz	CAS-No.: 14808-60-7	99-99.8	Eye Irrit. 2B, H320 Carc. 1A, H350 STOT SE 3, H335 STOT RE 2, H373
aluminium oxide, non-fibrous	CAS-No.: 1344-28-1	0.322	Not classified
potassium oxide	CAS-No.: 12136-45-7	0.105	Not classified
iron(III) oxide	CAS-No.: 1309-37-1	0.048	Not classified
calcium oxide	CAS-No.: 1305-78-8	0.033-0.04	Skin Corr. 1C, H314 Eye Dam. 1, H318 STOT SE 3, H335
titanium(IV) oxide; [crystalline solid or in powder form containing less than 1 % particles with aerodynamic diameter ≤ 10 µm]	CAS-No.: 13463-67-7	0.024	Carc. 2, H351
magnesium oxide	CAS-No.: 1309-48-4	0.02-0.024	Eye Irrit. 2B, H320 STOT SE 3, H335
sodium monoxide	CAS-No.: 1313-59-3	0.01	Not classified

Full text of hazard classes and H-statements : see section 16

### 3.2. Mixtures

Not applicable

# Silica Sand #60

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 4 First aid measures

#### 4.1. Description of necessary first-aid measures

First-aid measures general	: IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor/physician if you feel unwell.
First-aid measures after skin contact	: Wash skin with plenty of water.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center/doctor/physician if you feel unwell.
Personal protection for first-aid responders.	: First aid workers will be equipped with suitable personal protective equipment.

#### 4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after inhalation	: May cause respiratory irritation.
Symptoms/effects after skin contact	: None under normal conditions. Dust may cause irritation in skin folds or by contact in combination with tight clothing.
Symptoms/effects after eye contact	: Mild eye irritation.
Symptoms/effects after ingestion	: None under normal conditions.

#### 4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment	: Treat symptomatically.
-----------------------------------	--------------------------

### SECTION 5: Fire-fighting measures

#### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam.
Unsuitable extinguishing media	: Do not use a heavy water stream.

#### 5.2. Specific hazards arising from the chemical

Fire hazard	: No fire hazard.
Explosion hazard	: No direct explosion hazard.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

#### 5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

### SECTION 6 Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material-damage.
------------------	---

#### For non-emergency personnel

Protective equipment	: Wear recommended personal protective equipment.
Emergency procedures	: Only qualified personnel equipped with suitable protective equipment may intervene. Do not breathe dust/fume/gas/mist/vapors/spray.

# Silica Sand #60

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
- Emergency procedures : Evacuate unnecessary personnel.
- Environmental precautions : Avoid release to the environment. Notify authorities if product enters sewers or public waters.

### 6.2. Methods and materials for containment and cleaning up

- For containment : Using a clean shovel, put the material in a dry container and cover without compressing it.
- Methods for cleaning up : Mechanically recover the product. Notify authorities if product enters sewers or public waters.
- Other information : Dispose of materials or solid residues at an authorized site.

For further information refer to section 13

## SECTION 7 Handling and storage

### 7.1. Precautions for safe handling

- Precautions for safe handling : Ensure good ventilation of the work station. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Provide local exhaust or general room ventilation. Wear personal protective equipment. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with skin and eyes.
- Hygiene measures : Separate working clothes from town clothes. Launder separately. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
- Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.

### 7.2. Conditions for safe storage, including incompatibilities

- Technical measures : Keep in a cool, well-ventilated place away from heat.
- Storage conditions : Store locked up. Store in a well-ventilated place. Keep container tightly closed.
- Packaging materials : Store always product in container of same material as original container.

## SECTION 8 Exposure controls/personal protection

### 8.1. Control parameters

quartz (14808-60-7)	
USA - OSHA - Occupational Exposure Limits	
Local name	Quartz (Respirable) (Silica: Crystalline)
Remark (OSHA)	Table Z-3. For OSHA PEL (TWA): Use formulas: (250 / (%SiO <sub>2</sub> +5)) for mppcf and (10 mg/m <sup>3</sup> / (%SiO <sub>2</sub> +2)) for mg/m <sup>3</sup> . CAS No. source: eCFR Table Z-1.
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-3 Mineral Dusts
iron(III) oxide (1309-37-1)	
USA - OSHA - Occupational Exposure Limits	
Local name	Iron oxide fume
OSHA PEL TWA	10 mg/m <sup>3</sup>
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

# Silica Sand #60

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

aluminium oxide, non-fibrous (1344-28-1)	
<b>USA - ACGIH - Occupational Exposure Limits</b>	
ACGIH® TLV® TWA	1 mg/m <sup>3</sup> (Respirable fraction)
<b>USA - OSHA - Occupational Exposure Limits</b>	
Local name	alpha-Alumina
OSHA PEL TWA	15 mg/m <sup>3</sup> (Total dust) 5 mg/m <sup>3</sup> (Respirable fraction)
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
calcium oxide (1305-78-8)	
<b>USA - ACGIH - Occupational Exposure Limits</b>	
ACGIH® TLV® TWA	2 mg/m <sup>3</sup>
magnesium oxide (1309-48-4)	
<b>USA - OSHA - Occupational Exposure Limits</b>	
Local name	Magnesium oxide fume - Total Particulate
OSHA PEL TWA	15 mg/m <sup>3</sup>
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.  
Environmental exposure controls : Avoid release to the environment.

### 8.3. Individual protection measures, such as personal protective equipment

#### Personal protective equipment:

Wear recommended personal protective equipment.

<b>Hand protection:</b>
Protective gloves
<b>Eye protection:</b>
Safety glasses
<b>Skin and body protection:</b>
Wear suitable protective clothing
<b>Respiratory protection:</b>
[In case of inadequate ventilation] wear respiratory protection.

#### Personal protective equipment symbol(s):



## SECTION 9 Physical and chemical properties

### 9.1. Basic physical and chemical properties

Physical state : Solid

# Silica Sand #60

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Color	: Mixture contains one or more component(s) which have the following color(s): Colourless to white Red-brown to black White to grey Pure substance: colourless to white-grey Unpurified: yellow to brown Commercial substance: yellow to brown Colourless or white White to white-grey Pure substance: white Unpurified: coloured Colourless
Odor	: There may be no odor warning properties, odor is subjective and inadequate to warn of overexposure. Mixture contains one or more component(s) which have the following odor: Odourless
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: Not applicable
Boiling point	: No data available
Flash point	: Not applicable
Flammability (solid, gas)	: Non flammable.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: Not applicable
Decomposition temperature	: No data available
Viscosity, kinematic	: Not applicable
Explosion limits	: Not applicable
Particle characteristics	: No data available

### 9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

## SECTION 10 Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# Silica Sand #60

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 11 Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity (oral) : No data available  
Acute toxicity (dermal) : No data available  
Acute toxicity (inhalation) : No data available

<b>iron(III) oxide (1309-37-1)</b>	
LD50 oral rat	> 10000 mg/kg body weight (Rat, Male, Experimental value, Oral)
LC50 Inhalation - Rat	5.05 mg/l (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Male / female, Experimental value, Inhalation (aerosol), 14 day(s))
ATE US (vapors)	5.05 mg/l/4h
ATE US (dust, mist)	5.05 mg/l/4h
<b>aluminium oxide, non-fibrous (1344-28-1)</b>	
LD50 oral rat	> 15900 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral, 14 day(s))
LC50 Inhalation - Rat	> 2.3 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Experimental value, Inhalation (aerosol), 14 day(s))
<b>calcium oxide (1305-78-8)</b>	
LD50 oral rat	> 2000 mg/kg body weight (OECD 425: Acute Oral Toxicity: Up-and-Down Procedure, Rat, Female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	> 2500 mg/kg body weight (EU Method B.3: Acute toxicity (dermal), 24 h, Rabbit, Male / female, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat	> 6.04 mg/l (OECD 436: Acute inhalation toxicity-acute toxic class method, 4 h, Rat, Male / female, Experimental value, Inhalation (dust), 15 day(s))
<b>magnesium oxide (1309-48-4)</b>	
LD50 oral rat	> 5000 mg/kg (Rat, Literature study, Oral)
LD50 dermal rabbit	> 2000 mg/kg body weight (Rabbit, Literature study, Dermal)
<b>titanium(IV) oxide; [crystalline solid or in powder form containing less than 1 % particles with aerodynamic diameter ≤ 10 µm] (13463-67-7)</b>	
LD50 oral rat	> 5000 mg/kg body weight (OECD 425: Acute Oral Toxicity: Up-and-Down Procedure, Rat, Female, Experimental value, Oral, 14 day(s))
LC50 Inhalation - Rat	5.09 mg/l (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Male, Experimental value, Inhalation (dust), 14 day(s))
ATE US (vapors)	5.09 mg/l/4h
ATE US (dust, mist)	5.09 mg/l/4h
Skin corrosion/irritation	: No data available
<b>quartz (14808-60-7)</b>	
pH	6 – 7
<b>iron(III) oxide (1309-37-1)</b>	
pH	7 (5 %)
<b>aluminium oxide, non-fibrous (1344-28-1)</b>	
pH	9 – 10.5 (aqueous suspension, 33 %)

# Silica Sand #60

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

calcium oxide (1305-78-8)	
pH	12.5 (0.13 %, 20 °C)
magnesium oxide (1309-48-4)	
pH	11 (10 %)
titanium(IV) oxide; [crystalline solid or in powder form containing less than 1 % particles with aerodynamic diameter ≤ 10 µm] (13463-67-7)	
pH	7 (aqueous suspension, 10 %)
potassium oxide (12136-45-7)	
pH	No data available in the literature

Serious eye damage/irritation : Causes eye irritation.

quartz (14808-60-7)	
pH	6 – 7
iron(III) oxide (1309-37-1)	
pH	7 (5 %)
aluminium oxide, non-fibrous (1344-28-1)	
pH	9 – 10.5 (aqueous suspension, 33 %)
calcium oxide (1305-78-8)	
pH	12.5 (0.13 %, 20 °C)
magnesium oxide (1309-48-4)	
pH	11 (10 %)
titanium(IV) oxide; [crystalline solid or in powder form containing less than 1 % particles with aerodynamic diameter ≤ 10 µm] (13463-67-7)	
pH	7 (aqueous suspension, 10 %)
potassium oxide (12136-45-7)	
pH	No data available in the literature

Respiratory or skin sensitization : No data available

Germ cell mutagenicity : No data available

Carcinogenicity : May cause cancer.

quartz (14808-60-7)	
IARC group	1 - Carcinogenic to humans

Reproductive toxicity : No data available

STOT-single exposure : May cause respiratory irritation.

quartz (14808-60-7)	
STOT-single exposure	May cause respiratory irritation.
calcium oxide (1305-78-8)	
STOT-single exposure	May cause respiratory irritation.

# Silica Sand #60

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>magnesium oxide (1309-48-4)</b>	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: May cause damage to organs through prolonged or repeated exposure.
<b>quartz (14808-60-7)</b>	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: No data available
<b>Silica Sand #60</b>	
Viscosity, kinematic	Not applicable
<b>iron(III) oxide (1309-37-1)</b>	
Viscosity, kinematic	Not applicable (solid)
<b>aluminium oxide, non-fibrous (1344-28-1)</b>	
Viscosity, kinematic	Not applicable (solid)
<b>calcium oxide (1305-78-8)</b>	
Viscosity, kinematic	Not applicable (solid)
<b>magnesium oxide (1309-48-4)</b>	
Viscosity, kinematic	Not applicable (solid)
<b>titanium(IV) oxide; [crystalline solid or in powder form containing less than 1 % particles with aerodynamic diameter ≤ 10 µm] (13463-67-7)</b>	
Viscosity, kinematic	Not applicable (solid)
<b>potassium oxide (12136-45-7)</b>	
Viscosity, kinematic	Not applicable (solid)
Symptoms/effects after inhalation	: May cause respiratory irritation.
Symptoms/effects after skin contact	: None under normal conditions. Dust may cause irritation in skin folds or by contact in combination with tight clothing.
Symptoms/effects after eye contact	: Mild eye irritation.
Symptoms/effects after ingestion	: None under normal conditions.

## SECTION 12 Ecological information

### 12.1. Ecotoxicity

Ecology - general	: The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	: No data available
Hazardous to the aquatic environment, long-term (chronic)	: No data available

<b>iron(III) oxide (1309-37-1)</b>	
EC50 - Crustacea [1]	> 100 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)
<b>aluminium oxide, non-fibrous (1344-28-1)</b>	
LC50 - Fish [1]	> 100 mg/l (96 h, Salmo trutta, Literature study)
EC50 - Crustacea [1]	> 100 mg/l (48 h, Daphnia magna, Literature study)

# Silica Sand #60

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>calcium oxide (1305-78-8)</b>	
LC50 - Fish [1]	51 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Read-across, GLP)
EC50 - Crustacea [1]	49 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Read-across, Locomotor effect)
ErC50 algae	185 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Read-across, GLP)

<b>titanium(IV) oxide; [crystalline solid or in powder form containing less than 1 % particles with aerodynamic diameter ≤ 10 µm] (13463-67-7)</b>	
LC50 - Fish [1]	> 300 mg/l (Danio rerio, Fresh water, Literature study, Nominal concentration)
EC50 - Crustacea [1]	> 100 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)

<b>potassium oxide (12136-45-7)</b>	
LC50 - Fish [1]	918 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Labeo rohita, Semi-static system, Fresh water, Experimental value, GLP)
EC50 96h - Algae [1]	1368 mg/l (ECOSAR v1.00, Algae, Fresh water, QSAR)

## 12.2. Persistence and degradability

<b>Silica Sand #60</b>	
Persistence and degradability	Rapidly degradable

<b>quartz (14808-60-7)</b>	
Persistence and degradability	Biodegradability: not applicable, Not established.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable

<b>iron(III) oxide (1309-37-1)</b>	
Persistence and degradability	Biodegradability: not applicable, Adsorbs into the soil, Not established.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)

<b>aluminium oxide, non-fibrous (1344-28-1)</b>	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)

<b>calcium oxide (1305-78-8)</b>	
Persistence and degradability	Biodegradability: not applicable, Not established.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)

# Silica Sand #60

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>magnesium oxide (1309-48-4)</b>	
Persistence and degradability	Biodegradability: not applicable, No (test)data on mobility of the substance available, Not established.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)
<b>sodium monoxide (1313-59-3)</b>	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable
<b>titanium(IV) oxide; [crystalline solid or in powder form containing less than 1 % particles with aerodynamic diameter ≤ 10 µm] (13463-67-7)</b>	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)
<b>potassium oxide (12136-45-7)</b>	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)
<b>12.3. Bioaccumulative potential</b>	
<b>quartz (14808-60-7)</b>	
Partition coefficient n-octanol/water (Log Pow)	Not applicable
Bioaccumulative potential	No bioaccumulation data available. Not established.
<b>iron(III) oxide (1309-37-1)</b>	
Bioaccumulative potential	No bioaccumulation data available. Not established.
<b>aluminium oxide, non-fibrous (1344-28-1)</b>	
Bioaccumulative potential	Not bioaccumulative.
<b>calcium oxide (1305-78-8)</b>	
Bioaccumulative potential	Not bioaccumulative. Not established.
<b>magnesium oxide (1309-48-4)</b>	
Bioaccumulative potential	Bioaccumulation: not applicable. Not established.
<b>sodium monoxide (1313-59-3)</b>	
Bioaccumulative potential	No bioaccumulation data available.
<b>titanium(IV) oxide; [crystalline solid or in powder form containing less than 1 % particles with aerodynamic diameter ≤ 10 µm] (13463-67-7)</b>	
Bioaccumulative potential	Not bioaccumulative.

# Silica Sand #60

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

potassium oxide (12136-45-7)	
Bioaccumulative potential	Not bioaccumulative.

### 12.4. Mobility in soil

iron(III) oxide (1309-37-1)	
Surface tension	Not applicable (solid)
Ecology - soil	Adsorbs into the soil.

aluminium oxide, non-fibrous (1344-28-1)	
Surface tension	Not applicable (water solubility < 1 mg/l)
Ecology - soil	No (test)data on mobility of the substance available.

calcium oxide (1305-78-8)	
Surface tension	No data available in the literature
Ecology - soil	No (test)data on mobility of the substance available.

magnesium oxide (1309-48-4)	
Surface tension	No data available in the literature
Ecology - soil	No (test)data on mobility of the substance available.

titanium(IV) oxide; [crystalline solid or in powder form containing less than 1 % particles with aerodynamic diameter ≤ 10 µm] (13463-67-7)	
Surface tension	No data available in the literature
Ecology - soil	Low potential for mobility in soil.

potassium oxide (12136-45-7)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.1 (log Koc, SRC PCKOCWIN v2.0, QSAR)
Ecology - soil	Highly mobile in soil.

### 12.5. Other adverse effects

Ozone	: No data available
Fluorinated greenhouse gases	: No

## SECTION 13 Disposal considerations

Regional waste regulation	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Comply with applicable regulations for solid waste disposal. Disposal must be done according to official regulations.
Additional information	: Do not re-use empty containers.

## SECTION 14 Transport information

### 14.1. UN number

UN-No. (DOT)	: Not applicable
UN-No. (TDG)	: Not applicable

# Silica Sand #60

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

UN-No. (IMDG) : Not applicable  
UN-No. (IATA) : Not applicable

### 14.2. UN Proper Shipping Name

Proper Shipping Name (DOT) : Not applicable  
Proper Shipping Name (TDG) : Not applicable  
Proper Shipping Name (IMDG) : Not applicable  
Proper Shipping Name (IATA) : Not applicable

### 14.3. Transport hazard class(es)

**DOT**  
Transport hazard class(es) (DOT) : Not applicable

**TDG**  
Transport hazard class(es) (TDG) : Not applicable

**IMDG**  
Transport hazard class(es) (IMDG) : Not applicable

**IATA**  
Transport hazard class(es) (IATA) : Not applicable

### 14.4. Packing group

Packing group (DOT) : Not applicable  
Packing group (TDG) : Not applicable  
Packing group (IMDG) : Not applicable  
Packing group (IATA) : Not applicable

### 14.5. Environmental hazards

Other information : No supplementary information available.

### 14.6. Transport in bulk

Not applicable

### 14.7. Special precautions for user

**DOT**  
Not applicable

**TDG**  
Not applicable

**IMDG**  
Not applicable

**IATA**  
Not applicable

## SECTION 15 Regulatory information

### 15.1. Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory, except for:

sodium monoxide	CAS-No. 1313-59-3	0.01%
-----------------	-------------------	-------

# Silica Sand #60

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 15.2. International regulations

#### CANADA

##### quartz (14808-60-7)

Listed on the Canadian DSL (Domestic Substances List)

##### iron(III) oxide (1309-37-1)

Listed on the Canadian DSL (Domestic Substances List)

##### aluminium oxide, non-fibrous (1344-28-1)

Listed on the Canadian DSL (Domestic Substances List)

##### calcium oxide (1305-78-8)

Listed on the Canadian DSL (Domestic Substances List)

##### magnesium oxide (1309-48-4)

Listed on the Canadian DSL (Domestic Substances List)

##### titanium(IV) oxide; [crystalline solid or in powder form containing less than 1 % particles with aerodynamic diameter $\leq 10 \mu\text{m}$ ] (13463-67-7)

Listed on the Canadian DSL (Domestic Substances List)

##### potassium oxide (12136-45-7)

Listed on the Canadian DSL (Domestic Substances List)

#### EU-Regulations

No additional information available

#### National regulations

##### quartz (14808-60-7)

Listed on IARC (International Agency for Research on Cancer)

##### titanium(IV) oxide; [crystalline solid or in powder form containing less than 1 % particles with aerodynamic diameter $\leq 10 \mu\text{m}$ ] (13463-67-7)

Listed on IARC (International Agency for Research on Cancer)

### 15.3. State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

Component	State or local regulations
quartz(14808-60-7)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
iron(III) oxide(1309-37-1)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List

# Silica Sand #60

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Component	State or local regulations
aluminium oxide, non-fibrous(1344-28-1)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
calcium oxide(1305-78-8)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
magnesium oxide(1309-48-4)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
titanium(IV) oxide; [crystalline solid or in powder form containing less than 1 % particles with aerodynamic diameter $\leq 10 \mu\text{m}$ ](13463-67-7)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
potassium oxide(12136-45-7)	U.S. - New Jersey - Right to Know Hazardous Substance List

### SECTION 16 Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Issue date : 2/27/2026

Full text of hazard classes and H-statements	
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage
H320	Causes eye irritation
H335	May cause respiratory irritation
H350	May cause cancer.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.